



AllTapeSuppliesB.V.

Technical Data Sheet

DSC825HM

Double Sided Cloth Tapes

Description

This is a double sided cloth tape with scrim cloth carrier coated with a hotmelt adhesive and a dark yellow siliconized paper liner.

The tape has a very good initial adhesion as well as an excellent stability. It can be used on a wide variety of substrates.



Applications

Economy grade double sided carpet tape

Carrier and Adhesive

Cloth carrier cloth of 35% cotton / 65 % polyester
Synthetic rubber based adhesive
Yellow siliconized paper liner

Technical Details

PROPERTIES	VALUE	TEST METHOD
Thickness (Total with liner)	240 micron	AFERA 5006
Thickness Liner	0.65 - 0.70 micron	AFERA 5006
Tensile strength	35 N/cm	AFERA 5004
Adhesion to Steel	> 6 N/cm	AFERA 5001
Elongation at Break	20 %	AFERA 5004
Service temperature range	-5°C - 60°C	
Colour	White	

Storage : Clean and dry in a well ventilated area, preferably at a temperature between 15°C and 25°C.

Rev. Jan 24, 2012

Disclaimer : The above information is given in good faith, but the user should insure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. ATS All Tape Supplies B.V. cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications. All rolls made by ATS All Tape Supplies B.V. meet Afera's 4027 cutting tolerance +/- 0.8mm.