

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Extra security sealing, packaging and mending of “hard-to-stick-to” surfaces
- > Splicing
- > Used where a biodegradable tape is needed

ADVANTAGES AND BENEFITS

- > Adhesive properties allow it to stick to “hard-to-stick-to” surfaces
- > High tensile strength makes it an excellent choice for splicing

CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: Transparent, biodegradable, hand-tearable, cellulose film

Adhesive: High tack, natural rubber

COLOR(S)



Clear (CLR)



STANDARD WIDTH(S)

12 mm 18 mm 24 mm

STANDARD LENGTH(S)

66 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

| | STANDARD | METRIC |
|-----------------------------|-----------------|--------------|
| Tensile Strength | 18 lbs/in width | 31.5 N/10 mm |
| Adhesion to Stainless Steel | 54 oz/in width | 5.91 N/10 mm |
| Thickness | 1.7 mils | 0.04 mm |
| Elongation | 5 % | 5 % |
| Maximum Temperature | 265 F | 129 C |

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

A-A-113D, Type 1, Class A

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.