

## SCP081RS

## Masking Tapes

### Description

This Crepe paper tape is manufactured with pressure sensitive rubber-resin adhesive. It is very conformable and has good tensile strength and strong holding. The SCP081RS also has good tape-on-tape adhesion and is solvent, water and oil resistant. It can be used on surfaces like glass, aluminium, steel, paper, plastics, rubber moldings, chrome parts, wood and other flat surfaces. It removes easily without staining or leaving residue.



### Applications

- Automobile painting
- Other applications where baking is required with temperatures up to 85°C

### Carrier and Adhesive

Pale beige creped paper carrier  
Rubber resin adhesive

### Technical Details

PROPERTIES	VALUE
Thickness	157,5 micron
Adhesion to backing	1,2 N/cm
Adhesion to steel	2,75 N/cm
Tensile strength	32,4 N/cm
Elongation	7,5%
Temperature range	Up to 85°C

**Storage :** Clean and dry in a well ventilated area, preferably at a temperature between 15°C and 25°C.

*Disclaimer : The above information is given in good faith, but the user should insure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. ATS All Tape Supplies cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.*