

GP 100

Light Duty Gum
Paper Tape

Shurtape®

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Light duty packaging applications
- > Internal packaging for items placed in a secondary container

ADVANTAGES AND BENEFITS

- > Aggressive adhesive that becomes part of the box
- > 100% recyclable/biodegradable

CONSTRUCTION

Overall Grade/Function: Light duty

Backing: Kraft paper

Adhesive: Starch fortified, odorless, non-toxic, water activated

COLOR(S)



Natural (NAT)



White (WHI)

STANDARD WIDTH(S)

2 ½ in 3 in

STANDARD LENGTH(S)

600 ft

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Paper Sheet (Weight)	57 lbs	25.8 kg
MD Tensile Strength	40 lbs/in width	70.1 N/10 mm
CD Tensile Strength	26 lbs/in width	45.5 N/10 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

Conforms to ASTM D5749 Type II, Grade B Specification - replaced CID A-A-1492B, CID A-A-1671, PPP-T-45

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.