

P- 670

Premium Grade  
Polyethylene Coated Cloth Tape

Shurtape®

## TECHNICAL DATA

### TYPICAL APPLICATIONS

- > HVAC duct work sealing
- > Protection, splicing, bundling, seaming, and sealing
- > Higher tensile and easy tear are required

### ADVANTAGES AND BENEFITS

- > High adhesion and tack
- > Waterproof backing
- > Hand tearable
- > Delamination resistant
- > Conformable

### CONSTRUCTION

Overall Grade/Function: Premium Grade

Backing: Polyethylene coated cloth

Adhesive: Synthetic rubber

### COLOR(S)



Black (BLK)



White (WHI)



### STANDARD WIDTH(S)

24 mm    48 mm    72 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	38 lbs/in width	66.6 N/10 mm
Adhesion to Stainless Steel	95 oz/in width	10.40 N/10 mm
Thickness	11.0 mils	0.280 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.