

## CP 150

Painter's Mate  
Green Masking Tape

# Shurtape®

### TECHNICAL DATA

#### TYPICAL APPLICATIONS

- > For use on glass, metal, wood, walls, trim, baseboards and window frames
- > Safe to use with all paints, as well as most lacquers and varnishes

#### ADVANTAGES AND BENEFITS

- > Quality performance
- > Leaves clean, straight paint lines
- > Leaves no adhesive transfer up to 8 days in direct sunlight

#### CONSTRUCTION

Overall Grade/Function: Multi-purpose

Backing: Green crepe paper

Adhesive: Rubber based

#### COLOR(S)

 Green (GRN)

#### STANDARD WIDTH(S)

6 mm    18 mm    24 mm    36 mm    48 mm    72 mm

#### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

#### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	17 lbs/in width	30 N/10 mm
Adhesion to Stainless Steel	24 oz/in width	2.6 N/10 mm
Thickness	5.7 mils	0.14 mm
Elongation	11 %	11 %
Adhesion to Backing	5 oz/in width	0.5 N/10 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

#### APPLICABLE SPECIFICATIONS

ASTM D6123/D6123M-97

#### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

