

## DST150SA Double Sided Tissue Tapes

### Description

Double sided tissue tape with a solvent acrylic adhesive, strong holding power and good temperature resistance.



### Applications

- Paper splicing
- Plastic bag sealing
- Name plates bonding
- Nailless carton bonding

### Carrier and Adhesive

Tissue carrier  
Solvent acrylic adhesive  
120 g/m2 white siliconized paper liner

### Technical Details

PROPERTIES	VALUE	TEST METHOD
Total thickness	150 micron	
Initial tack	<120mm with ball#14	GB/T 4852-2002
Peeling strength	>6,8 N/cm	GB/T 2792-1998
Holding power @ 23°C	> 800 minutes	GB/T 4851-1998
@ 80°C	> 20 minutes	
Temperature resistance	-30°C up to +120°C	
Adhesion to steel	≥7-13 N/25mm	

**Storage :** Clean and dry in a well ventilated area, preferably at a temperature between 15°C and 25°C.

*Disclaimer : The above information is given in good faith, but the user should insure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. ATS All Tape Supplies cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.*