

TECHNICAL DATA

**TYPICAL APPLICATIONS**

- > Splice, insulate and bind wiring harnesses

**ADVANTAGES AND BENEFITS**

- > High tensile strength and elongation
- > Non-corrosive adhesive

**CONSTRUCTION**

Overall Grade/Function: UL Listed Electrical Tape  
 Backing: Matte finish, soft polyvinylchloride (SPVC)  
 Adhesive: Non-corrosive, natural rubber

**COLOR(S)**

	Blue (BLU)		Orange (ORG)
	Green (GRN)		Red (RED)
	Brown (BRN)		White (WHI)
	Yellow (YEL)		



**STANDARD WIDTH(S)**

¾ in            19 mm

**STANDARD LENGTH(S)**

66 ft            20 m

Contact your Shurtape sales representative for other available sizes.

**PHYSICAL PROPERTIES**

	STANDARD	METRIC
Tensile Strength	12.6 lbs/in width	22.07 N/10 mm
Adhesion to Stainless Steel	13 oz/in width	1.42 N/10 mm
Thickness	6.8 mils	0.17 mm
Elongation	380 %	380 %
Service Temperature Range	20 F to 176 F	-7 C to 80 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

**APPLICABLE SPECIFICATIONS**

UL Listed for Insulation Tapes

**STORAGE & USAGE CONDITIONS**

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.