

PC 622

Premium Grade  
Cloth Duct Tape

Shurtape®

## TECHNICAL DATA

### TYPICAL APPLICATIONS

- > Motorsports
- > Silk screening
- > Plastering
- > Stucco masking
- > HVAC duct systems
- > Bundling, seaming, sealing & splicing

### ADVANTAGES AND BENEFITS

- > Waterproof backing
- > High tensile strength
- > Conformable
- > Excellent holding power

### CONSTRUCTION

**Overall Grade/Function:** Premium Grade

**Backing:** Waterproof, polyethylene film with a polyester/cotton blend cloth carrier

**Adhesive:** Natural Rubber

### COLOR(S)



Black (BLK)



Red (RED)



White (WHI)



Silver (SIL)



Olive Drab (OLV)

### STANDARD WIDTH(S)

48 mm    72 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	40 lbs/in width	70.1 N/10 mm
Adhesion to Stainless Steel	55 oz/in width	6.02 N/10 mm
Thickness	12.5 mils	0.32 mm
Elongation	10 %	10 %
Service Temperature Range	50 F to 200 F	10 C to 93 C

### APPLICABLE SPECIFICATIONS

Tested in accordance with UL723; Flame Spread Index 10; Smoke Development Index 10.

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

"Shurtape" is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PC622-09-07/2010