

## Technical Data Sheet

# DST120SA Double Sided Tissue Tapes

### Description

This double sided tissue tape has excellent heat and temperature resistance, strong adhesion and holding power. It adheres strongly to various types of backing and is especially suitable for camber surfaces.



### Applications

- Paper splicing
- Nameplates and Membrane switches
- Die Cutting
- Electronic components

### Carrier and Adhesive

14 g/m<sup>2</sup> Tissue carrier  
Solvent acrylic adhesive  
120 g/m<sup>2</sup> White siliconised paper liner

### Technical Details

PROPERTIES	VALUE	TEST METHOD
Total thickness	120 micron	
Initial tack	<100mm with ball#14	GB/T 4852-2002
Peeling strength	>6,4 N/25mm	GB/T 2792-1998
Holding power	@ 23°C @ 80°C @ 120°C @ 180°C	>1440 minutes > 200 minutes 80-180 minutes 20 minutes
		GB/T 4851-1998

**Storage :** Clean and dry in a well ventilated area, preferably at a temperature between 15°C and 25°C.

*Disclaimer : The above information is given in good faith, but the user should insure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. ATS All Tape Supplies cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.*