

**TECHNICAL DATA**

**TYPICAL APPLICATIONS**

- > Rough Surfaces
- > Heavy Repairs
- > Bottom Board Tape in Manufacturing Housing

**ADVANTAGES AND BENEFITS**

- > Extra thick adhesive for quick stick on rough surfaces
- > Superior Strength High-count cloth
- > Waterproof backing provides durable protection

**CONSTRUCTION**

Overall Grade/Function: Specialty Grade

Backing: Polyethylene

Adhesive: Natural Rubber

**COLOR(S)**



Metallic Silver (MSL)



**STANDARD WIDTH(S)**

48 mm

**STANDARD LENGTH(S)**

40 yd

Contact your Shurtape sales representative for other available sizes.

**PHYSICAL PROPERTIES**

	STANDARD	METRIC
Tensile Strength	47 lbs/in width	82.3 N/10 mm
Adhesion to Stainless Steel	110 oz/in width	12.04 N/10 mm
Thickness	17 mils	.43 mm
Elongation	11 %	11 %
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

**APPLICABLE SPECIFICATIONS**

**STORAGE & USAGE CONDITIONS**

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.