

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Masking for wood and metal

ADVANTAGES AND BENEFITS

- > Flexible and conformable
- > Good quick stick
- > Strips cleanly in hot or cold environments
- > Prevents primer flake-off and paint build-up

CONSTRUCTION

Overall Grade/Function: Performance Grade

Backing: Crepe paper

Adhesive: High Adhesion, rubber-based adhesive

COLOR(S)



Natural (NAT)

STANDARD WIDTH(S)

18 mm 24 mm 36 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	22 lbs/in width	38.5 N/10 mm
Adhesion to Stainless Steel	39 oz/in width	4.27 N/10 mm
Thickness	6.7 mils	0.17 mm
Elongation	8.5 %	8.5 %
Service Temperature Range *	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

ASTM D6123/D6123M-97 Type I; PPP-T-42C, Type I

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

* Strips cleanly after one hour. May be submitted to higher temperature for shorter periods of time.