



AllTapeSupplies

Technical Data Sheet

JFP150SA Masking tape



KEY FEATURES

- Made of Japanese flat paper uniformly coated with acrylic adhesive
- Masking for a boundary fine line when painting
- Holding masking paper and cur sheet
- Masking tape for multiple layer paint jobs
- Masking tape for automotive after market
- Good for use in combination with water based paints
- Not suitable for application on polycarbonate or natural stone (marble)

CARRIER AND ADHESIVE

- Japanese flat paper carrier
- Acrylic adhesive

TECHNICAL DETAILS

Properties	Value
Total Thickness	87 micron
Adhesion strenght	1,7 N/cm
Tensile strenght	34,66 N/cm
Elongation at break	3%
Temp. resistance	up to 100°C (20 min)
UV resistance	up to 4 months
Unwinding force	1,5 N/cm
Backing to backin	0,7 N/cm
ahesion strenght	
Weight	81 g/m ²

STORAGE

Clean and dry in a well ventilated area, preferably at a temperature between 15°C and 25°C.

Disclaimer: The above information is given in good faith, but when te user should insure himself that the performance of the product is sufficient for this application. The quoted values are average and should not be taken as maximun or minimum values for specific purposes. ATS All Tape Supplies cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.

information sales@alltape.eu
www.alltape.eu