

## Technical Data Sheet

# DST100HM Double Sided Tissue Tapes

### Description

Good performance, general purpose double sided tissue tape with a hotmelt adhesive



### Applications

- General applications
- Plastic bag sealing
- Paper sticking

### Carrier and Adhesive

Non woven tissue carrier  
Synthetic rubber adhesive  
95 grams/m2 white siliconized paper liner

### Technical Details

PROPERTIES	VALUE		Test Method
Total thickness	100 micron		
Initial tack (#14 steel ball)	Summer: >100 mm	Winter: > 120 mm	GB/T 4852-2002
Peeling strength	Summer: 19N/25mm	Winter: 15N/25mm	GB/T 2792-1998
Holding power	Summer: >120 min.	Winter: >48 min.	GB/T 4851-1998
Temperature range	Up to +80°C		
Adhesion to steel	≥8-20 N/25mm		

**Storage :** Clean and dry in a well ventilated area, preferably at a temperature between 15°C and 25°C.

*Disclaimer : The above information is given in good faith, but the user should insure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. ATS All Tape Supplies cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.*