

Technical Data Sheet

DSV970SA

Double Sided PVC Tapes

Description

This is a double sided mounting tape with a strong initial tack, solvent acrylic adhesive, with a PVC carrier. It has got an excellent all-round performance. Suitable for rough and embossed surfaces.



Applications

Fixing plastic and wooden mouldings, bonding and laminating flexible and rigid materials
Fixing point of display materials, print finishing and general applications

Carrier and Adhesive

100 micron white PVC carrier
Solvent acrylic adhesive
Glassine paper liner (90 gms)

Technical Details

PROPERTIES	VALUE	TEST METHOD
Total thickness	225 micron	
Film thickness	100 micron	
Initial tack	<100 mm with ball#14	GB/T 4852-2002
Peeling strength	>18 N/25 mm	GB/T 2792-1998
Holding power	@ 23°C @ 80°C	GB/T 4851-1998
	>2880 minutes	
	>20 minutes	

Storage : Clean and dry in a well ventilated area, preferably at a temperature between 15°C and 25°C.

Disclaimer : The above information is given in good faith, but the user should insure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. ATS All Tape Supplies cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.