

DF 642

General Purpose, Industrial Grade
Double Faced Cloth Tape

Shurtape®

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Industrial holding, mounting and splicing
- > Installation of carpet

ADVANTAGES AND BENEFITS

- > Conformable to irregular surfaces
- > Adheres to a variety of substrates

CONSTRUCTION

Overall Grade/Function: Industrial Grade

Backing: Polyester/cotton blend cloth

Adhesive: Synthetic rubber adhesive

Liner: Siliconized, flat paper release liner

COLOR(S)



White (WHI)

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

23 m 33 m

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	32 lbs/in width	56.0 N/10 mm
Adhesion to Stainless Steel	29 oz/in width	3.17 N/10 mm
Thickness	12.0 mils	0.30 mm
Elongation	8 %	8 %
Service Temperature Range	50 F to 225 F	10 C to 107C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.