

## Technical Data Sheet

# FLP124HM

# Flatpaper Tapes

### Description

This is a packaging and splicing kraft flatback paper tape with synthetic rubber adhesive.



### Applications

Hand and machine carton sealing  
Splicing of various substrates  
General purpose packaging, binding, holding, tabbing, reinforcing, banding and patching tape for a variety of substrates.

### Carrier and Adhesive

Kraft, flatback paper  
Synthetic Rubber (Hot melt) Adhesive

### Technical Details

PROPERTIES	VALUE	TEST METHOD
Total thickness	135 micron	
Total weight	116 g/m <sup>2</sup> (± 3 g)	
Adhesive weight	28 g/m <sup>2</sup> (± 2 g)	
Peel adhesion	9,65 N/cm	ASTM-D3330
Tensile strength	23,5 N/cm	ASTM-D3759
Elongation	5%	ASTM-D3759
Holding Power	>30 hr.	ASTM-D3654

**Storage :** Clean and dry in a well ventilated area, preferably at a temperature between 15°C and 25°C.

*Disclaimer : The above information is given in good faith, but the user should insure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. ATS All Tape Supplies cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.*