

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Masking for drywall and other delicate surfaces
- > Painting and general purpose applications for which a low tack, high performance tape is needed
- > Apply to clean, smooth surfaces free of oil and dirt
- > Masking for faux finishing

ADVANTAGES AND BENEFITS

- > Flexible and conformable
- > Strips cleanly

CONSTRUCTION

Overall Grade/Function: Performance Grade

Backing: Crepe paper

Adhesive: Delicate surface, Acrylic-based adhesive

COLOR(S)



Violet (VLT)

STANDARD WIDTH(S)

24 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	25 lbs/in width	43.8 N/10 mm
Adhesion to Stainless Steel	8 oz/in width	0.88 N/10 mm
Thickness	5.1 mils	0.13 mm
Elongation	5 %	5 %

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

ASTM D6123/D6123M-97

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.