

DF 191

Painters Mate
Double-Sided Dropcloth Tape

Shurtape®

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Ceilings and walls

ADVANTAGES AND BENEFITS

- > Holds plastic dropcloth in place while painting, ceilings, walls, etc.
- > Can be used with all paints, most lacquers and varnishes on properly prepared, fully cured surfaces
- > Leaves sharp clean paint lines with less edge bleed

CONSTRUCTION

Overall Grade/Function: Multi-purpose

Backing: Smooth crepe paper

Adhesive: Rubber based

COLOR(S)



Green (GRN)

STANDARD WIDTH(S)

36 mm

STANDARD LENGTH(S)

25 m

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	18 lbs/in width	31 N/10 mm
Adhesion to Stainless Steel	30 oz/in width	3.3 N/10 mm
Thickness	6 mils	0.15 mm
Elongation	11 %	11 %

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.