

## TECHNICAL DATA

## TYPICAL APPLICATIONS

- > Designed for industrial, commercial and residential paint markets for use on metal, vinyl, glass, plastic and rubber

## ADVANTAGES AND BENEFITS

- > Easy unwind and controlled mid-range adhesion that meet the requirements of industrial and professional painters
- > Excellent adhesion and quick stick to metal, vinyl, glass, plastic and rubber
- > Good resistance to solvents and heat
- > Good performance on variety of surfaces and irregular shapes
- > Easy, clean surface release and sharp, clean paint lines
- > Use by hand or with a masker



## CONSTRUCTION

Overall Grade/Function: Industrial Grade

Backing: Crepe paper

Adhesive: Rubber-based adhesive

## COLOR(S)



Light Yellow (LTY)

## STANDARD WIDTH(S)

18 mm    24 mm    36 mm    48 mm

## STANDARD LENGTH(S)

46 m

Contact your Shurtape sales representative for other available sizes.

## PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	19 lbs/in width	33.3 N/10 mm
Adhesion to Stainless Steel	33 oz/in width	3.61 N/10 mm
Thickness	5.3 mils	0.13 mm
Elongation	8 %	8 %
Adhesion to Backing	15 oz/in	1.62 N/10 mm
Service Temperature Range	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

## APPLICABLE SPECIFICATIONS

ASTM D6123/D6123M-97; CID A-A-883B, Type I

## STORAGE &amp; USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.