

DUC170RS

Duct Tapes

Description

The DUC170RS is a PE-coated cloth tape with a rubber based adhesive. High quality purpose for irregular surface, stationery, water proof, vinyl repair, protecting, and bundling. Moisture barrier for both indoor and outdoor application.



Applications

- Carton sealing
- Surface protecting
- Bookbinding
- and many other general purposes

Carrier and Adhesive

PE coated 70 mesh woven cloth
Natural rubber adhesive

Technical Details

PROPERTIES	VALUE
Thickness	300 micron
Adhesion to steel	4,3 N/cm +/- 0,4
Rewinding force	19,6 N/50mm
Ball tack	10 cm, ball #20
Tensile strength	54,9 N/cm
Holding power	60 min @ 25mmx25mm/40°C
Elongation at break	10%
Temperature range	-35°C up to +80°C
Storage life	6 months

Storage : Clean and dry in a well ventilated area, preferably at a temperature between 15°C and 25°C.

Disclaimer : The above information is given in good faith, but the user should insure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. ATS All Tape Supplies cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.