

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Seaming and sealing of bottom board materials used in the mobile/manufactured housing industry
- > Repairing of bottom board holes either formed by rodents or fabricators (i.e. plumbers, electricians, etc.) during set-up and construction
- > Protection of metal parts or surfaces in metal and/or plastic peening operations.

ADVANTAGES AND BENEFITS

- > Waterproof backing
- > High tack
- > Withstands extreme temperature fluctuations
- > Superior holding power
- > High durability

CONSTRUCTION

Overall Grade/Function: Super bottom board tape

Backing: Waterproof, polyethylene film with a polyester/cotton blend cloth carrier

Adhesive: Natural rubber

COLOR(S)



Black (BLK)

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

33 m

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	30 lbs/in width	52.5 N/10 mm
Adhesion to Stainless Steel	100 oz/in width	10.95 N/10 mm
Thickness	17 mils	0.43 mm
Elongation	10 %	10 %
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

Tested in accordance with UL723; Flame Spread Index 15; Smoke Development Index 20.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

"Shurtape" is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PC658-06/12/2008