

TECHNICAL DATA

TYPICAL APPLICATIONS

- > For all axial lead and sequencing applications

ADVANTAGES AND BENEFITS

- > Designed for superior elongation, tensile and tear resistance
- > Very easy unwind
- > High temperature resistance
- > Heavy gauge construction and ultra-release allow tracking in varied equipment configurations

CONSTRUCTION

Overall Grade/Function: Premium Grade

Backing: Crepe paper

Adhesive: Moderate tack, rubber-based adhesive

COLOR(S)



Natural (NAT)



Blue (BLU)



STANDARD WIDTH(S)

6 mm $\frac{3}{8}$ in 57 in

STANDARD LENGTH(S)

163 m 2000 m 3218 m 1500 yd

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	28 lbs/in width	49.0 N/10 mm
Adhesion to Stainless Steel	50 oz/in width	5.47 N/10 mm
Thickness	7.1 mils	0.18 mm
Elongation	9 %	9 %

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

ASTM D6123/D6123M-97

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.