

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Hand and machine carton sealing
- > Splicing of various substrates
- > General purpose packaging, binding, holding, tabbing, reinforcing, banding and patching tape for a variety of substrates

ADVANTAGES AND BENEFITS

- > Strong, flexible and conformable backing
- > High cross-directional tensile strength
- > Aggressive, high tack adhesive with excellent holding power
- > Excellent quick stick, particularly effective in cold weather
- > Tape color blends well with kraft cartons
- > Resists curling, abrasion, water, solvents and oil

CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: Extensible, kraft, flatback paper

Adhesive: High tack, rubber-based adhesive

COLOR(S)



Kraft (KFT)



STANDARD WIDTH(S)

1 3/4 in 18 mm 24 mm 36 mm 48 mm 72 mm

STANDARD LENGTH(S)

55 yd 55 m 439 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	37 lbs/in width	64.8 N/10 mm
Adhesion to Stainless Steel	88 oz/in width	9.63 N/10 mm
Thickness	6.2 mils	0.16 mm
Elongation	6 %	6 %
Service Temperature Range	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.