

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Over-lamination
- > Label protection
- > Light carton closure paper repair/mending and holding applications
- > Ideal for use with counter and desk dispenser units

ADVANTAGES AND BENEFITS

- > Glossy, brilliantly clear
- > Will not yellow with age – nor discolor packages or objects after being applied
- > Lightweight, yet strong
- > Easily dispensed
- > Stronger than cellophane or acetate



CONSTRUCTION

Backing: Biaxially oriented polypropylene film

Adhesive: Solvent based acrylic

COLOR(S)



Clear (CLR)

STANDARD WIDTH(S)

½ in ¾ in 1 in

STANDARD LENGTH(S)

36 yd 72 yd

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	20 lbs/in width	35.0 N/10 mm
Adhesion to Stainless Steel	25 oz/in width	2.74 N/10 mm
Thickness	2.6 mils	0.066 mm
Elongation	14 %	14 %
Applicable Temperature Range	20 F to 110 F	-7 C to 43 C
Service Temperature Range	-20 F to 180 F	-28 C to 83 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.