

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Gaffer's tape
- > Holding wiring, lighting and props
- > Color coding

ADVANTAGES AND BENEFITS

- > High adhesion and tack
- > Clean removal
- > Conformable
- > Hand tearable
- > Wide variety of colors





CONSTRUCTION

Overall Grade/Function: Specialty Gaffer's Grade

Backing: Vinyl coated cloth

Adhesive: Synthetic rubber

COLOR(S)

	Fluorescent Yellow (FLY)		Fluorescent Green (FLG)
	Fluorescent Orange (FLO)		Fluorescent Pink (FLP)

STANDARD WIDTH(S)

24mm 48mm

STANDARD LENGTH(S)

55m

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	46 lbs/in width	80.6 N/10 mm
Adhesion to Stainless Steel	50 oz/in width	5.47 N/10 mm
Thickness	12.0 mils	0.3 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.