

P- 69

Premium Grade
Polyethylene Cloth Tape

Shurtape®

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Waterproof sealing of containers and ductwork
- > Protection, splicing, bundling, seaming, and sealing
- > When high tensile, easy tear, and conformability are needed

ADVANTAGES AND BENEFITS

- > Waterproof backing
- > High adhesion and tack
- > High tensile strength
- > Hand tearable
- > Conformable

CONSTRUCTION

Overall Grade/Function: Premium Grade

Backing: Polyethylene coated cloth

Adhesive: Synthetic rubber

COLOR(S)

 Olive Drab (OLV)

STANDARD WIDTH(S)

1 in 2 in

STANDARD LENGTH(S)

60 yd

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	43 lbs/in width	75.3 N/10 mm
Adhesion to Stainless Steel	134 oz/in width	14.67 N/10 mm
Thickness	12.0 mils	0.30 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

A-A-1586A; ASTM-5486M-99, Type IV

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.