

PC 657

Premium Grade  
Cloth Duct Tape

Shurtape®

## TECHNICAL DATA

### TYPICAL APPLICATIONS

- > Manufactured housing to seam bottom boards
- > Sealing HVAC ducts
- > Metal peening
- > Motorsports 200 mph duct tape

### ADVANTAGES AND BENEFITS

- > Waterproof backing
- > Excellent holding power
- > High tack
- > Withstands extreme temperature fluctuations
- > Durable

### CONSTRUCTION

Overall Grade/Function: Premium Grade

Backing: Waterproof, polyethylene film with a polyester/cotton blend cloth carrier

Adhesive: Natural rubber

### COLOR(S)



### STANDARD WIDTH(S)

48 mm 72 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	30 lbs/in width	52.5 N/10 mm
Adhesion to Stainless Steel	80 oz/in width	8.76 N/10 mm
Thickness	14.5 mils	0.37 mm
Elongation	10 %	10 %
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE SPECIFICATIONS

Tested in accordance with UL 723 Listed – Flame Spread Index 15, Smoke Development Index 40

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

"Shurtape" is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PC657-06/12/2008

