



AllTapeSuppliesB.V.

Technical Data Sheet

DUC200HM

Duct Tape

Description

DUC200HM is a general purpose grade cloth tape with a quick and high initial tack. The product is very flexible and will conform itself to irregular surfaces.



Application

Bundling
Holding
Temporary repairs

Carrier and Adhesive

Backing: 37-40 mesh PE laminated synthetic cloth
Adhesive: synthetic rubber / resins

Technical Details

PROPERTIES

VALUE

Thickness	200 my (+/- 10%)
Adhesive to Stainless Steel 180 angle	≥ 20 N/2,5 cm
Tensile strength	30 N/cm (+/- 5%)
Service Temperature range	up to 60°C

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and performed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Storage : Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

Disclaimer : The above information is given in good faith, but the user should insure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. ATS All Tape Supplies cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.