

Technical Data Sheet

DUC180RS

Duct Tapes

Description

The DUC180RS is a PE-coated superior performance cloth tape with a rubber based adhesive. High quality purpose for irregular surface, stationery, water proof, vinyl repair, protecting, and bundling. Moisture barrier for both indoor and outdoor application. Available in: Black, white, silver, red, orange, yellow, dark green, light green, olive green, dark blue, light blue, s. blue.

Colours available on request: Brown, beige, pink, purple.

Applications

- Carton sealing
- Surface protecting
- Bookbinding
- and many other general purposes



Carrier and Adhesive

PE coated 80 mesh woven cloth Natural rubber adhesive

Technical Details

PROPERTIES VALUE

Thickness 320 micron
Adhesion to steel 4,3 N/cm +/- 0,4
Rewinding force 19,6 N/50mm
Ball tack 10 cm, ball #20

Tensile strength 63 N/cm

Holding power 60 min @ 25mmx25mm/40℃

Elongation at break 10%

Temperature range -35℃ up to +80℃

Storage life 6 months

Storage: Clean and dry in a well ventilated area, preferably at a temperature between 15℃ and 25℃.

Disclaimer: The above information is given in good faith, but the user should insure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes.

ATS All Tape Supplies cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.