

TECHNICAL DATA

TYPICAL APPLICATIONS

- > For use on glass, vinyl and wood where clean removal is required after up to fourteen days of exposure to direct sunlight
- > NOTE: Not recommended for use on wallpaper, unpainted wallboard, ceiling tile or with uncured coatings.

ADVANTAGES AND BENEFITS

- > Excellent 14 day UV resistance
- > Good performance for a variety of applications that require easy removal

CONSTRUCTION

Overall Grade/Function: 14-day UV resistant

Backing: Crepe paper

Adhesive: Acrylic

COLOR(S)

 Blue (BLU)

STANDARD WIDTH(S)

18 mm 24 mm 36 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	24 lbs/in width	42.0 N/10 mm
Adhesion to Stainless Steel	19 oz/in width	2.08 N/10 mm
Thickness	5.7 mils	0.14 mm
Elongation	6 %	6 %
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

ASTM D6123/D6123M-97

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

