

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Holding, seaming and sealing HVAC sheet metal and flex ducts, exhaust vents and preformed insulation
- > Industrial holding, splicing, protecting and packaging

ADVANTAGES AND BENEFITS

- > Waterproofing backing
- > Excellent conformability and tack
- > Easy unwind and tear
- > Excellent holding power





CONSTRUCTION

Overall Grade/Function: Contractor Grade

Backing: Waterproof, polyethylene film with a polyester/cotton blend cloth carrier

Adhesive: Natural Rubber

COLOR(S)

	Black (BLK)		Silver Printed (SPT)
	Silver (SIL)		Black Printed (BPT)

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	27 lbs/in width	47.3 N/10 mm
Adhesion to Stainless Steel	55 oz/in width	6.02 N/10 mm
Thickness	11.5 mils	0.29 mm
Elongation	10 %	10 %
Service Temperature Range	50 F to 200 F	10 C to 93 C

APPLICABLE SPECIFICATIONS

Tested in accordance with UL723; Flame Spread Index 5; Smoke Development Index 5.

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.