

PC 609

Industrial Grade
Cloth Duct Tape

Shurtape®

TECHNICAL DATA

TYPICAL APPLICATIONS

- > HVAC industry on sheet metal, flex duct and thermal insulation
- > Manufactured housing to seam bottom boards and for patching, seaming and sealing
- > Packaging, bundling, holding, wrapping and waterproofing

ADVANTAGES AND BENEFITS

- > Excellent holding power
- > Good conformability
- > Easy unwind and tear
- > Waterproof backing





CONSTRUCTION

Overall Grade/Function: Industrial Grade

Backing: Waterproof polyethylene film with a polyester/cotton cloth carrier

Adhesive: Natural rubber

COLOR(S)

	Black (BLK)		Silver Printed (SPT)
	Silver (SIL)		Red (RED)

STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	22 lbs/in width	38.5 N/10 mm
Adhesion to Stainless Steel	55 oz/in width	6.02 N/10 mm
Thickness	10 mils	0.27 mm
Elongation	15 %	15 %
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

Tested in accordance with UL723; Flame Spread Index 0, Smoke Development Index 0; Green Point Contributor Product

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

