

## Technical Data Sheet

### HSB346AC

### Double Sided Tapes

#### Description

The HSB346AC is especially designed for permanent bonding in interior and exterior applications. This can replace riveting, welding, liquid glues and other permanent fasteners. It is also suitable for various kinds of substances, such as metal, wood, glass and many plastics. High tack and excellent shear performance.



#### Applications

- Fixing exterior trims and bodyside mouldings
- Signs and panels
- Emblem and badge mounting & rear view mirrors
- Interior and exterior use
- Panel mounting

#### Carrier and Adhesive

Low density Polyethylene (LDPE)  
Red, LDPE Liner

#### Technical Details

PROPERTIES	VALUE
Thickness	0,25 mm
Foam Density	830 kg/m <sup>2</sup>
Adhesion to steel	17,7 N/cm
Tensile strength	64 N/cm
Temperature range	-30°C / +120°C
Solvent resistance	No degradation
UV-Resistance	Good
Moisture resistance	Excellent

**Storage :** Clean and dry in a well ventilated area, preferably at a temperature between 15°C and 25°C.

*Disclaimer : The above information is given in good faith, but the user should insure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. ATS All Tape Supplies cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.*