

PE 555

Multi-Purpose  
Polyethylene Film Tape

Shurtape®

## TECHNICAL DATA

### TYPICAL APPLICATIONS

- > Surface protection
- > Color coding
- > Splicing and seaming on pipe fitting covers

### ADVANTAGES AND BENEFITS

- > Waterproof
- > Excellent tear characteristics
- > Excellent adhesion

### CONSTRUCTION

Overall Grade/Function: Multi-purpose

Backing: Polyethylene film

Adhesive: Clear, synthetic rubber

### COLOR(S)



Red (RED)

### STANDARD WIDTH(S)

48 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.



### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	30 lbs/in width	35.0 N/10 mm
Adhesion to Stainless Steel	67 oz/in width	7.30 N/10 mm
Thickness	9.0 mils	0.23 mm
Elongation	100 %	100 %
Service Temperature Range	32 F to 160 F	0 C to 71 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.