

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Seals spiral and rectangular galvanized ductwork for clean room installations, duct storage & transportation
- > Protects ducts from contaminants and contamination occurring from dust, dirt, moisture & insects.
- > For hand use applications

ADVANTAGES AND BENEFITS

- > Protects ducts from contaminants and contamination occurring from dust, dirt, moisture & insects.
- > Increased elongation from other films for duct sealants
- > Easy removal without residue
- > Cold weather adhesive

CONSTRUCTION

Overall Grade/Function: Protective Film, Weather Resistant, Medium Tack
 Backing: Polyolefin Film
 Adhesive: Emulsion Acrylic

COLOR(S)



Translucent/ Matte (CLR)

STANDARD WIDTH(S)

24 inch 609.6mm

36 inch 914.4mm

STANDARD LENGTH(S)

200 ft 60.96M

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tape Gauge	2.4 mils	0.06mm
Adhesion to Stainless Steel	14 oz/in width	1.53 N/10 mm
Adhesion to Backing	5.8 oz	.63 N/10mm
Tensile MD	7.8 lb/in width	13.66 N/10mm
Elongation MD	1200%	1200%
Service Temperature	-26 °F to 260 °F	-32 °C to 127 °C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

