

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Corrosion protection for metal and plastic pipe
- > For use on underground pipe installations

ADVANTAGES AND BENEFITS

- > 10 mil film thickness
- > Non-corrosive pressure sensitive adhesive
- > Excellent moisture resistance and conformability

CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: 10 mil, PVC film

Adhesive: Rubber-based



COLOR(S)



Black Printed (BPT)

STANDARD WIDTH(S)

50 mm

STANDARD LENGTH(S)

30 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	25 lbs/in width	43.09 N/10 mm
Adhesion to Stainless Steel	20 oz/in width	2.15 N/10 mm
Thickness	10.0 mils	0.254 mm
Elongation	200 %	200 %
Dielectric Strength	1250 volts/mil	

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

UPC Approved

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.