

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Protection of labels, instructions, etc.
- > Industrial and production laminating, joining and protection of various substrates

ADVANTAGES AND BENEFITS

- > High tack adhesive
- > Excellent clarity and visibility of substrate under tape
- > Provides moisture-proof seal
- > Resists bacteria, fungi, solvents and weathering
- > Excellent shelf life
- > Will not discolor or crack
- > Usable in broad temperature range

CONSTRUCTION

Overall Grade/Function: Premium Grade, Label Protection and General Purpose

Backing: Extra clear, biaxially oriented polypropylene film (BOPP)

Adhesive: Clear, solvent based acrylic



COLOR(S)



Clear (CLR)

STANDARD WIDTH(S)

4 in 6 in

STANDARD LENGTH(S)

72 yd

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	20 lbs/in width	35.0 N/10mm
Adhesion to Stainless Steel	23 oz/in width	2.52 N/10mm
Thickness	1.8 mils	.05 mm
Elongation	140 %	140 %
Service Temperature Range	-20 F to 180 F	-29 C to 82 C
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Adhesion to Backing	15 oz/in width	1.73 N/10mm
Adhesion to Kraft	9.0 oz/in width	0.89 N/10mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.