

VF 719

Economy Grade, Printable, UPVC  
Film Packaging Tape

Shurtape®

## TECHNICAL DATA

### TYPICAL APPLICATIONS

- > Sealing cartons, particularly those with recycled fiber content, heavy ink coverage or rough surfaces
- > Use when sub-freezing temperatures and/or moisture are factors

### ADVANTAGES AND BENEFITS

- > Aggressive adhesive reduces application time because excessive rub-down is not necessary
- > Excellent choice when sub-freezing temperatures and moisture are factors
- > May be used on printed stock and recycled paper

### CONSTRUCTION

Overall Grade/Function: Economy Grade, Printable

Backing: Unplasticized polyvinylchloride film (UPVC)

Adhesive: Natural rubber

### COLOR(S)

Clear (CLR)  White (WHI)

Tan (TAN)



### STANDARD WIDTH(S)

48 mm

### STANDARD LENGTH(S)

50 m

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	26 lbs/in width	44.7 N/10 mm
Adhesion to Stainless Steel	12 oz/in width	1.31 N/10 mm
Thickness	2.0 mils	0.05 mm
Elongation	70 %	70 %
Service Temperature Range	0 F to 150 F	-18 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE SPECIFICATIONS

CID A-A-1689B, Type II

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

"Shurtape" is a registered trademark of Shurtape Technologies, LLC

Form# TDS-VF719-08/28/2006