

VP 415

General Purpose, Striped
SPVC Film Tape "Warning Stripe Tape"

Shurtape®

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Floor, lane and aisle marking
- > Sealing/Bundling
- > Identification of safety and caution areas

ADVANTAGES AND BENEFITS

- > Non-corrosive adhesive
- > Backing is flexible and resistant to acid, alkalides, oils, moisture, humidity and corrosion
- > Abrasion-resistant backing
- > Meets OSHA requirements for hazard markings – Black/Yellow (physical hazard)

CONSTRUCTION

Overall Grade/Function: General Purpose, Striped

Backing: Striped, stabilized, plasticized, soft polyvinylchloride film (SPVC)

Adhesive: Natural rubber



COLOR(S)



Black /Yellow (BKY)

Black/White (BKW)

STANDARD WIDTH(S)

50mm

STANDARD LENGTH(S)

33m

*Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	15 lbs./in. width	26.3 N/10mm
Adhesion to Stainless Steel	12 oz./in. width	1.31 N/10mm
Thickness	6.6 mils	.17 mm
Elongation	200 %	200 %
Service Temperature Range	20 F to 140 F	-7 C to 60 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

PPP-T-66E, Type I, Class 2 (Cancelled 1/6/97, superseded by A-A-1689B, Type I Class 2)

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

"Shurtape" is a registered trademark of Shurtape Technologies, LLC

Form# TDS VP415 8/26/2009