

WP 240

Production Grade, Reinforced  
Water Activated Tape

Shurtape®

## TECHNICAL DATA

### TYPICAL APPLICATIONS

- > Medium duty carton sealing for normal manufacturing and handling stress when a custom message is desired

### ADVANTAGES AND BENEFITS

- > Aggressive adhesive that becomes part of the box
- > 100% recyclable
- > Customized messages
- > Optimal security to prevent pilferage

### CONSTRUCTION

Overall Grade/Function: Production Grade

Backing: Reinforced kraft paper

Adhesive: Starch fortified, odorless, non-toxic, water activated

### COLOR(S)

☒ Natural (NAT) ☐ White (WHI)

### STANDARD WIDTH(S)

Contact your Shurtape sales representative for available sizes.

### STANDARD LENGTH(S)

Contact your Shurtape sales representative for available sizes.



### PHYSICAL PROPERTIES

	STANDARD	METRIC
Top Sheet (weight)	24 lbs	10.8 kg
Bottom Sheet (weight)	24 lbs	10.8 kg
Laminate	Hot Melt	Hot Melt
MD Glass	75/110 Denier	75/110 Denier
MD Pattern	1-1-1	1-1-1
MD Spacing	5/8 in	1.6 cm
MD Tensile	52 lbs/in	91.1 N/10 mm
CD Tensile	30 lbs/in	51.7 N/10 mm
CD Filament	PET	PET
CD Spacing	1.25 in	3.17 cm
Service Temperature Range	-20 F to 120 F	-28.8 C to 48.8 C
Application Temperature Range	33 F to 110 F	-0.6 C to 48.8 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE SPECIFICATIONS

Rule 41

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

"Shurtape" is a registered trademark of Shurtape Technologies, LLC

Form# TDS-WP240-08/28/2006